



TRANSFORMERS RENTAL GUIDE
 Working with you to make your event happen

110v Tool Transformer



Size (kVA)	3 peak, 1.5 continuous
Incoming Phase	1Ø
Outgoing Phase	1Ø
Incoming Connections	16A Cee Form
Outgoing Connections	2x 16A Cee Form
Input Voltage	240
Output Voltage	110
Dimensions - Length (mm)	250
Width (mm)	230
Height (mm)	260
Weight (kg)	16.5
Wheels	X
Fork Slots	X
ORDER CODE	TR110RA

2 kVA UK to US Transformer



Size (kVA)	2
Incoming Phase	1Ø
Outgoing Phase	1Ø
Incoming Connections	16A single phase Cee Form
Outgoing Connections	2x Edison (US)
Input Voltage	240
Output Voltage	110
Dimensions - Length (mm)	430
Width (mm)	260
Height (mm)	305
Weight (kg)	25
Wheels	X
Fork Slots	X
ORDER CODE	TR02

110v Tool Transformer



Size (kVA)	5 peak, 2.5 continuous
Incoming Phase	1Ø
Outgoing Phase	1Ø
Incoming Connections	32A Cee Form
Outgoing Connections	1x 32A, 2x 16A Cee Form
Input Voltage	240
Output Voltage	110
Dimensions - Length (mm)	390
Width (mm)	320
Height (mm)	290
Weight (kg)	44.5
Wheels	X
Fork Slots	X
ORDER CODE	TR110RB

4 kVA UK to US Transformer + Edison



Size (kVA)	4
Incoming Phase	3Ø
Outgoing Phase	1Ø & 3Ø
Incoming Connections	32/3 Cee Form
Outgoing Connections	1x 32/3 Hubble 6 x Edison (US)
Input Voltage	415
Output Voltage	120 / 208
Dimensions - Length (mm)	720
Width (mm)	510
Height (mm)	550
Weight (kg)	80
Wheels	✓
Fork Slots	X
ORDER CODE	TRGF

6 kVA UK to US Transformer



Size (kVA)	6
Incoming Phase	3Ø
Outgoing Phase	3Ø
Incoming Connections	32/3 Cee Form
Outgoing Connections	32/3 Hubble (US)
Input Voltage	415
Output Voltage	208
Dimensions - Length (mm)	520
Width (mm)	520
Height (mm)	640
Weight (kg)	70
Wheels	✓
Fork Slots	✗
ORDER CODE	TR06

7 kVA Transformer



Size (kVA)	7
Incoming Phase	1Ø
Outgoing Phase	1Ø
Incoming Connections	32A Cee Form
Outgoing Connections	6x 110v 16A Cee Form
Input Voltage	240
Output Voltage	110 +/- 8.5%
Dimensions - Length (mm)	770
Width (mm)	540
Height (mm)	750
Weight (kg)	115
Wheels	✓
Fork Slots	✗
ORDER CODE	TR07

400 kVA Transformer



Size (kVA)	400
Incoming Phase	3Ø
Outgoing Phase	3Ø
Incoming Connections	Powerlock
Outgoing Connections	Powerlock
Input Voltage	415
Output Voltage	415 volts, stepped +/- 2.5% and 5%
Dimensions - Length (mm)	1665
Width (mm)	960
Height (mm)	1540
Weight (kg)	1850
Wheels	✓
Fork Slots	✓
ORDER CODE	TR400

Isolating Transformer



Size (kVA)	3 peak, 1.5 continuous
Incoming Phase	1Ø
Outgoing Phase	1Ø
Incoming Connections	16A Cee Form
Outgoing Connections	2x 16A Cee Form
Input Voltage	240
Output Voltage	240
Dimensions - Length (mm)	290
Width (mm)	210
Height (mm)	250
Weight (kg)	18
Wheels	✗
Fork Slots	✗
ORDER CODE	TRISO

30 kVA (US)Transformer



Size (kVA)	30
Incoming Phase	3Ø
Outgoing Phase	3Ø
Incoming Connections	125/3 Cee Form
Outgoing Connections	US colour Powerlock
Input Voltage	415
Output Voltage	120 / 208
Dimensions - Length (mm)	940
Width (mm)	840
Height (mm)	1030
Weight (kg)	383
Wheels	✓
Fork Slots	✗
ORDER CODE	TR30

100 kVA Transformer



Size (kVA)	100
Incoming Phase	3Ø
Outgoing Phase	3Ø
Incoming Connections	Powerlock
Outgoing Connections	Powerlock
Input Voltage	415
Output Voltage	415 volts, stepped +/- 2.5% and 5%
Dimensions - Length (mm)	1100
Width (mm)	720
Height (mm)	1380
Weight (kg)	750
Wheels	✓
Fork Slots	✓
ORDER CODE	TR100

225 kVA 3Ø to 1Ø Transformer



Size (kVA)	225
Incoming Phase	3Ø
Outgoing Phase	1Ø
Incoming Connections	Powerlock
Outgoing Connections	3x Single Phase Powerlock
Input Voltage	415
Output Voltage	240
Dimensions - Length (mm)	1870
Width (mm)	900
Height (mm)	1440
Weight (kg)	1675
Wheels	✗
Fork Slots	✓
ORDER CODE	TRCP