



EMERGENCY LIGHTING RENTAL GUIDE

Working with you to make your event happen

Emergency Exit (Non-Maintained)



| | |
|--------------------------|--|
| Dimensions - Length (mm) | 450 |
| Width (mm) | 230 |
| Depth (mm) | 195 |
| Weight (kg) | 3 |
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | 16A Cee Form |
| Wattage | 8 W |
| Operating Voltage | 240 |
| Unit Power Consumption | 8 W |
| Lamp | Compact Fluorescent |
| Battery Life | 90 min |
| IP Rating | IP65 |
| Variations | Emergency Exits can be Maintained/ Non-Maintained on request |
| Additional Notes | Non-Maintained: Light not lit when powered |
| Product ID | EE |
| ORDER CODE | EE |

Emergency Exit (Maintained)



| | |
|--------------------------|--|
| Dimensions - Length (mm) | 450 |
| Width (mm) | 230 |
| Depth (mm) | 195 |
| Weight (kg) | 3 |
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | 16A Cee Form |
| Wattage | 8 W |
| Operating Voltage | 240 |
| Unit Power Consumption | 8 W |
| Lamp | 8W flourescent |
| Battery Life | 90 min |
| IP Rating | IP65 |
| Variations | Emergency Exits can be Maintained/ Non-Maintained on request |
| Additional Notes | Maintained : Light lit when powered |
| Product ID | EEM |
| ORDER CODE | EEM |



Emergency Exit (Maintained/Non-Maintained Switchable LED Version)



| | |
|--------------------------|---|
| Dimensions - Length (mm) | 450 |
| Width (mm) | 230 |
| Depth (mm) | 195 |
| Weight (kg) | 3 |
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | 16A Cee Form |
| Wattage | 7 W |
| Operating Voltage | 240 |
| Unit Power Consumption | 7 W |
| Lamp | Multiple LEDs |
| Battery Life | 90 min |
| IP Rating | IP65 |
| Variations | Switchable M/NM |
| Additional Notes | Maintained: Light lit when powered. Non-Maintained: Light not lit when powered |
| Product ID | EES |
| ORDER CODE | EES |

Large Emergency Exit Pescara-G



| | |
|--------------------------|---|
| Dimensions - Length (mm) | 620 |
| Width (mm) | 455 |
| Depth (mm) | 100 |
| Weight (kg) | 9.4 |
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | 16A Cee Form |
| Wattage | 18 W |
| Operating Voltage | 240 |
| Unit Power Consumption | 18W |
| Lamp | 18 Watt T8 fluorescent |
| Battery Life | 90 min |
| IP Rating | IP65 |
| Variations | None |
| Additional Notes | 80m viewing distance ensures the item is suitable to applications where greater viewing distances are required. |
| Product ID | BEEM |
| ORDER CODE | BEEM |

Emergency Twin Head



| | |
|--------------------------|---|
| Dimensions - Length (mm) | 400 |
| Width (mm) | 420 |
| Depth (mm) | 130 |
| Weight (kg) | 10 |
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | 16A Cee Form |
| Wattage | 40W |
| Operating Voltage | 240 |
| Unit Power Consumption | 40W |
| Lamp | 2x 20W 12V B15 Auto Twinspot lamp |
| Battery Life | 90 min |
| IP Rating | IP20 |
| Variations | Unspecified |
| Additional Notes | Individual LED lamp health indicators. Lamp heads fully adjustable. 2x 12V7Ah lead acid batteries supplied. Fitted to rugged ABS Enclosure. |
| Product ID | TWH |
| ORDER CODE | TWH |



FESTOON LIGHTING RENTAL GUIDE

Working with you to make your event happen

Edison Screw Festoon 1m Spacing (Product ID - FE1)

| Length (m) | Connection Fitting | Lamp | Light Spacing (m) | Incoming Connection | Outgoing Connection | Wattage Per Lamp | ORDER CODE |
|------------|--------------------|--------|-------------------|---------------------|---------------------|------------------|----------------|
| 25 | Edison Screw | 6W LED | 1 | 16A | 16A | Max 15 W | FE 1-25 |
| 50 | Edison Screw | 6W LED | 1 | 16A | 16A | Max 15 W | FE 1-50 |
| | | | | | | | |

Edison Screw Festoon 3m Spacing (Product ID - FE3)

| Length (m) | Connection Fitting | Lamp | Light Spacing (m) | Incoming Connection | Outgoing Connection | Wattage Per Lamp | ORDER CODE |
|------------|--------------------|--------|-------------------|---------------------|---------------------|------------------|-----------------|
| 25 | Edison Screw | 6W LED | 3 | 16A | 16A | Max 60 W | FE 3-25 |
| 50 | Edison Screw | 6W LED | 3 | 16A | 16A | Max 60 W | FE 3-50 |
| 75 | Edison Screw | 6W LED | 3 | 16A | 16A | Max 60 W | FE 3-75 |
| 100 | Edison Screw | 6W LED | 3 | 16A | 16A | Max 60 W | FE 3-100 |

Edison Screw Festoon 5m Spacing (Product ID - FE5)

| Length (m) | Connection Fitting | Lamp | Light Spacing (m) | Incoming Connection | Outgoing Connection | Wattage Per Lamp | ORDER CODE |
|------------|--------------------|--------|-------------------|---------------------|---------------------|------------------|-----------------|
| 25 | Edison Screw | 6W LED | 5 | 16A | 16A | Max 60 W | FE 5-25 |
| 50 | Edison Screw | 6W LED | 5 | 16A | 16A | Max 60 W | FE 5-50 |
| 75 | Edison Screw | 6W LED | 5 | 16A | 16A | Max 60 W | FE 5-75 |
| 100 | Edison Screw | 6W LED | 5 | 16A | 16A | Max 60 W | FE 5-100 |

Additional Notes

Shorter lengths and spacing with ES or Bayonet are available on request. Please note LED is also available at 3.5 Watt BC or 6 Watt ES



EXTERIOR AND FLOOD LIGHT RENTAL GUIDE

Working with you to make your event happen



150W Enclosed Halogen Floodlight



| | |
|--------------------------|------------------|
| Incoming Connection | 16A |
| Wattage Lamp Type | 150W K12 |
| IP Rating | IP54 |
| Variations | None |
| Weight (kg) | 0.75 |
| Dimensions - Length (mm) | 135 |
| Width (mm) | 95 |
| Depth (mm) | 120 |
| Product ID | 150W TH |
| ORDER CODE | LEF-150TH |

500W Enclosed Halogen Floodlight



| | |
|--------------------------|---------------------------------|
| Incoming Connection | 16A |
| Wattage Lamp Type | 500W K1 |
| IP Rating | IP54 |
| Compatible with | 120W - 230W - 300W - 400W bulbs |
| Weight (kg) | 1.75 |
| Dimensions - Length (mm) | 180 |
| Width (mm) | 140 |
| Depth (mm) | 125 |
| Product ID | 500W TH |
| ORDER CODE | LEF-500TH |

1000W Enclosed Halogen Floodlight



| | |
|--------------------------|-------------------|
| Incoming Connection | 16A |
| Wattage Lamp Type | 1000W K4 |
| IP Rating | IP54 |
| Variations | None |
| Weight (kg) | 2.2 |
| Dimensions - Length (mm) | 250 |
| Width (mm) | 270 |
| Depth (mm) | 150 |
| Product ID | 1000W TH |
| ORDER CODE | LEF-1000TH |

1500W Enclosed Halogen Floodlight



| | |
|--------------------------|-------------------|
| Incoming Connection | 16A |
| Wattage Lamp Type | 1500W K5 |
| IP Rating | IP54 |
| Variations | None |
| Weight (kg) | 4 |
| Dimensions - Length (mm) | 350 |
| Width (mm) | 390 |
| Depth (mm) | 180 |
| Product ID | 1500W TH |
| ORDER CODE | LEF-1500TH |

70W Metal Halide Floodlight



| | |
|--------------------------|--|
| Incoming Connection | 16A |
| Wattage Lamp Type | 70W HQI-TS |
| IP Rating | IP65 |
| Colours Available | White - Sodium - Blue - Green - Magenta |
| Weight (kg) | 5.4 |
| Dimensions - Length (mm) | 370 |
| Width (mm) | 240 |
| Depth (mm) | 100 |
| Product ID | 70W MBI |
| ORDER CODE | LEF-70-(W-S-B-G-M Colour) |

150W Metal Halide Floodlight



| | |
|--------------------------|--|
| Incoming Connection | 16A |
| Wattage Lamp Type | 150W HQI-TS |
| IP Rating | IP65 |
| Colours Available | White - Sodium - Blue - Green - Magenta |
| Weight (kg) | 5.4 |
| Dimensions - Length (mm) | 370 |
| Width (mm) | 240 |
| Depth (mm) | 100 |
| Product ID | 150W MBI |
| ORDER CODE | LEF-150-(W-S-B-G-M Colour) |



250W Metal Halide Floodlight



| | |
|--------------------------|--|
| Incoming Connection | 16A |
| Wattage Lamp Type | 250W HQI-TS |
| IP Rating | IP65 |
| Colours Available | White - Sodium - Blue - Green - Magenta |
| Weight (kg) | 8 |
| Dimensions - Length (mm) | 500 |
| Width (mm) | 410 |
| Depth (mm) | 140 |
| Product ID | 250W MBI |
| ORDER CODE | LEF-250-(W-S-B-G-M Colour) |

400W Metal Halide Floodlight



| | |
|--------------------------|--|
| Incoming Connection | 16A |
| Wattage Lamp Type | 400W HQI-TS |
| IP Rating | IP65 |
| Colours Available | White - Sodium - Blue - Green - Magenta |
| Weight (kg) | 8.75 |
| Dimensions - Length (mm) | 500 |
| Width (mm) | 410 |
| Depth (mm) | 140 |
| Product ID | 400W MBI |
| ORDER CODE | LEF-400-(W-S-B-G-M Colour) |

70W SON Floodlight



| | |
|--------------------------|------------------|
| Incoming Connection | 16A |
| Wattage Lamp Type | 70W E27 ES |
| IP Rating | IP54 |
| Variations | None |
| Weight (kg) | 3.5 |
| Dimensions - Length (mm) | 370 |
| Width (mm) | 240 |
| Depth (mm) | 140 |
| Product ID | 70W SON |
| ORDER CODE | LEF-70SON |

GU10 Spike Light



| | |
|--------------------------|-------------------------------|
| Incoming Connection | 16A |
| Wattage Lamp Type | Up to 50W GU10 50W (max.) |
| IP Rating | IP65 |
| Variations | Various LED colours available |
| Weight (kg) | 0.75 |
| Dimensions - Length (mm) | 150 |
| Width (mm) | 100 |
| Depth (mm) | 100 |
| Product ID | SPIKE LIGHT |
| ORDER CODE | LEF-GU10SL |

PAR 38 Spike



| | |
|--------------------------|---|
| Incoming Connection | 16A |
| Wattage Lamp Type | 80W (120W White)* PAR 38 |
| IP Rating | IP44 |
| Variations | White* - Green - Blue - Yellow - Red |
| Weight (kg) | 1.16 |
| Dimensions - Length (mm) | 100 |
| Width (mm) | 130 |
| Depth (mm) | 90 |
| Product ID | PAR 38 |
| ORDER CODE | LEF-PAR38-(W-G-B-Y-R Colour) |

10W / 20W LED Floodlight



| | |
|--------------------------|--------------------------|
| Incoming Connection | 16A |
| Wattage Lamp Type | 10W / 20W LED |
| IP Rating | IP65 |
| Variations | Available in 20W |
| Weight (kg) | 0.75 |
| Dimensions - Length (mm) | 100 |
| Width (mm) | 130 |
| Depth (mm) | 90 |
| Product ID | 10W LED / 10W LED |
| ORDER CODE | 10W LED / 20W LED |



ROPE LIGHTING RENTAL GUIDE

Working with you to make your event happen

Neon Rope Light

| Length (m) | Incoming Connection | Wattage | Unit Power Consumption | IP Rating | Colour | ORDER CODE |
|------------|---------------------|------------------------|------------------------|-----------|--------|------------------|
| 45 | 16A | 16W Per metre (approx) | 16W per metre | IP44 | White | LRL-N-45W |
| 45 | 16A | 16W Per metre (approx) | 16W per metre | IP44 | Green | LRL-N-45G |
| 45 | 16A | 16W Per metre (approx) | 16W per metre | IP44 | Red | LRL-N-45R |
| 45 | 16A | 16W Per metre (approx) | 16W per metre | IP44 | Blue | LRL-N-45B |
| 45 | 16A | 16W Per metre (approx) | 16W per metre | IP44 | Orange | LRL-N-45O |
| 45 | 16A | 16W Per metre (approx) | 16W per metre | IP44 | Yellow | LRL-N-45Y |

LED Rope Light

| Length (m) | Incoming Connection | Wattage | Unit Power Consumption | IP Rating | Colour | ORDER CODE |
|------------|---------------------|-------------------------|------------------------|-----------|--------|------------------|
| 45 | 16A | 2.4W Per metre (approx) | 2.4W per metre | IP44 | Red | LRL-L-45R |
| 45 | 16A | 2.4W Per metre (approx) | 2.4W per metre | IP44 | Green | LRL-L-45G |



WORK LIGHT RENTAL GUIDE

Working with you to make your event happen

Desk Lamp



| | |
|--------------------------|--------------|
| Incoming Connection | 13A Plug Top |
| Lamp Type | E14 |
| Wattage | 40w Max |
| IP Rating | Unspecified |
| Weight (kg) | 0.75 |
| Dimensions - Length (mm) | N/A |
| Width (mm) | 130 |
| Depth (mm) | 140 |
| Height (mm) | 375 |
| Product ID | AP |
| ORDER CODE | AP |

5ft 58W Fluorescent Fitting



| | |
|--------------------------|--|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | 16A Cee Form |
| Wattage | 58W |
| IP Rating | IP65 |
| Weight (kg) | 3 |
| Dimensions - Length (mm) | 1570 |
| Width (mm) | 90 |
| Depth (mm) | 100 |
| Height (mm) | N/A |
| Additional Notes | The IP65 T8 Weatherproof Fluorescent Batten is a tough 5 foot, (or 6 foot twin) luminaire built for hard-wearing indoor and outdoor use and delivering widespread even illumination. ABS base with impact resistant polycarbonate diffuser. High frequency for flicker free operation and prolonged lamp life. |
| Product ID | LFF-5S |
| ORDER CODE | LFF-5S |

Slam Tube



| | |
|--------------------------|-------------------------------------|
| Incoming Connection | 16A Cee Form |
| Wattage Lamp Type | 72W 2x 36W compact fluorescent |
| IP Rating | IP44 |
| Weight (kg) | 2.55 |
| Dimensions - Length (mm) | 720 |
| Width (mm) | 110 |
| Depth (mm) | 110 |
| Height (mm) | N/A |
| Additional Notes | Suitable for use in hazardous areas |
| Product ID | LST-72 |
| ORDER CODE | LST-72 |

6ft 140W Twin Fluorescent Fitting



| | |
|--------------------------|---------------|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | 16A Cee Form |
| Wattage | 140W |
| IP Rating | IP65 |
| Weight (kg) | 7.2 |
| Dimensions - Length (mm) | 1870 |
| Width (mm) | 180 |
| Depth (mm) | 110 |
| Height (mm) | N/A |
| Product ID | LFF-6T |
| ORDER CODE | LFF-6T |

EST ⚡ 1999
Powerline

POWER DISTRIBUTION TEMPERATURE CONTROL



LIGHTING AND STUDIO FX RENTAL GUIDE

Working with you to make your event happen

— www —
THEPOWERLINE.CO.UK



ETC Source 4 Zoom



| | |
|----------------------------|--|
| Incoming Connection | 16A Cee Form |
| Lamp / IP Rating | 750W Max HPL - compact tungsten filament lamp - IP Rating IP22 |
| Power Options | 575W and 750W |
| Beam Angle | 25° - 50° |
| Weight (kg) | 8.5 |
| Dimensions - Length (mm) | 740 |
| Width (mm) | 290 |
| Depth (mm) | 300 |
| White Light / Colour Temp. | 3065K (based on 750W lamp) |

Rotating shutter assembly $\pm 25^\circ$, with stainless steel shutters.
Integral die cast colour frame / accessory holders and top mounted retainer.
Slot for glass or stainless steel gobos.
Slot with sliding cover for motorised gobo devices or optional iris.

| | |
|------------|--------------------|
| Product ID | S4 25/50 |
| ORDER CODE | LSL-S425/50 |

ETC S4 19°



| | |
|----------------------------|--|
| Incoming Connection | 16A Cee Form |
| Lamp / IP Rating | 750W Max HPL - compact tungsten filament lamp - IP Rating IP22 |
| Power Options | 575W and 750W |
| Beam Angle | 19° |
| Weight (kg) | 6.3 |
| Dimensions - Length (mm) | 135 |
| Width (mm) | 95 |
| Depth (mm) | 120 |
| White Light / Colour Temp. | 3065K (based on 750W lamp) |

Rotating shutter assembly $\pm 25^\circ$, with stainless steel shutters.
Two accessory slots, and a top mounted, gel frame retainer.
Slot for glass or stainless steel gobos.
Slot with sliding cover for motorized pattern devices or optional iris.
Interchangeable lens barrels permit selection of 5°, 10°, 19°, 26°, 36°, and 50° field angles.

| | |
|------------|-----------------|
| Product ID | S4 19 |
| ORDER CODE | LSL-S419 |

Par56 Long Nose



| | |
|----------------------------|---|
| Incoming Connection | 16A Cee Form |
| Lamp / IP Rating | CP available - IP Rating IP20 |
| Wattage | 300W |
| Beam Angle | Narrow to Wide, dependant on lamp Please specify requirement |
| Weight (kg) | 2.5 |
| Dimensions - Length (mm) | 410 |
| Width (mm) | 265 |
| Depth (mm) | 255 |
| White Light / Colour Temp. | 2750K |

PAR56 light fitting. Supplied with a slide-in gel frame and mounting bracket.

| | |
|------------|------------------|
| Product ID | LN PAR56 |
| ORDER CODE | LSL-P56LN |

Par64 6 lamp bar



| | |
|----------------------------|---|
| Incoming Connection | Socapex |
| Lamp / IP Rating | CP available - IP Rating IP20 |
| Power Options | 6x 500W or 6x 1000W |
| Beam Angle | Narrow to Wide, dependant on lamp Please specify requirement |
| Weight (kg) | 25 |
| Dimensions - Length (mm) | 2300 |
| Width (mm) | 265 |
| Depth (mm) | 450 |
| White Light / Colour Temp. | 2700K at 500W, 3200K at 1000W |

6 x Long nose Par64 installed on an internally wired bar with a Socapex inlet.

| | |
|------------|-------------------|
| Product ID | P64 6LB |
| ORDER CODE | LSL-P64-6X |



Par64 Long Nose



| | |
|----------------------------|---|
| Incoming Connection | 16A Cee Form |
| Lamp / IP Rating | CP available - IP Rating IP20 |
| Power Options | 500W and 1000W |
| Beam Angle | Narrow to Wide, dependant on lamp Please specify requirement |
| Weight (kg) | 3 |
| Dimensions - Length (mm) | 410 |
| Width (mm) | 265 |
| Depth (mm) | 255 |
| White Light / Colour Temp. | 2700K at 500W, 3200K at 1000W |

PAR64 (ParCan), the standard light source for bands and theatre. Supplied with a slide-in gel frame and mounting bracket.

| | |
|------------|------------------|
| Product ID | LN PAR64 |
| ORDER CODE | LSL-P64LN |

Par64 Short Nose



| | |
|----------------------------|---|
| Incoming Connection | 16A Cee Form |
| Lamp / IP Rating | CP available - IP Rating IP20 |
| Power Options | 500W and 1000W |
| Beam Angle | Narrow to Wide, dependant on lamp Please specify requirement |
| Weight (kg) | 2.5 |
| Dimensions - Length (mm) | 370 |
| Width (mm) | 265 |
| Depth (mm) | 255 |
| White Light / Colour Temp. | 2700K at 500W, 3200K at 1000W |

PAR64 Short nose light fitting, supplied with a slide-in gel frame.

| | |
|------------|------------------|
| Product ID | SN PAR64 |
| ORDER CODE | LSL-P64SN |

Par 16 Birdie



| | |
|----------------------------|-----------------------|
| Incoming Connection | 16A Cee Form |
| Lamp / IP Rating | GU10 - IP Rating IP20 |
| Power Options | 30W and 50W |
| Beam Angle | 30° |
| Weight (kg) | 0.4 |
| Dimensions - Length (mm) | 145 |
| Width (mm) | 80 |
| Depth (mm) | 125 |
| White Light / Colour Temp. | 2700K |
| Product ID | BIRDIE |
| ORDER CODE | LSL-P16B |

Par36 Pin Spot



| | |
|----------------------------|---|
| Incoming Connection | 16A Cee Form |
| Lamp / IP Rating | PAR 36 Screw Terminal IP Rating IP20 |
| Wattage | 30 W |
| Beam Angle | 15° |
| Weight (kg) | 0.6 |
| Dimensions - Length (mm) | 170 |
| Width (mm) | 160 |
| Depth (mm) | 150 |
| White Light / Colour Temp. | 3000K |
| Product ID | P36 PIN SPOT |
| ORDER CODE | LSL-P36 |



GEKKO Karesslite 100



| | |
|--------------------------|-------------------------------------|
| Incoming Connection | 16A Cee Form or 13A Plug at charger |
| Outgoing Connection | None |
| Wattage | 45W |
| Beam Angle | 50° |
| White/Colour Temperature | 3,200 - 5,600K |
| Lamp | Multiple LED |
| IP Rating | IP21 |
| Operating Voltage | 10 – 30 VDC |
| Power Consumption | 45W approx. |
| Power Options | PAG L96e Battery 14.8V 6.5Ah |
| Weight (kg) | 1.1 |
| Dimensions - Length (mm) | 310 |
| Width (mm) | 55 |
| Depth (mm) | 125 |
| Product ID | GEKKO KARESSLITE 100 |
| ORDER CODE | LSF-GK100 |

Lite Panels LP-1x1 Bi Color



| | |
|--------------------------|---|
| Incoming Connection | 16A Cee Form via transformer |
| Outgoing Connection | None |
| Wattage | 45W |
| Beam Angle | 50° |
| White/Colour Temperature | 3,200 - 5,600K |
| Lamp | LED |
| IP Rating | IP21 |
| Operating Voltage | 12 – 30 V |
| Power Consumption | 45W approx. |
| Power Options | 13a 230v AC-PSU, Battery LCA LP-100 21.6V 4.4Ah |
| Weight (kg) | 1.36 |
| Dimensions - Length (mm) | 405 |
| Width (mm) | 350 |
| Depth (mm) | 100 |
| Product ID | LITEPANELS LP-1x1 |
| ORDER CODE | LSF-LP1X1 |

Arri L7-C



| | |
|--------------------------|--|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | None |
| Wattage | 220W (max) |
| Beam Angle | 15° - 50° (Half Peak Angle) |
| White/Colour Temperature | 2,800 K - 10,000 K Continuously Variable Correlated Colour Temperature |
| Lamp | LED |
| IP Rating | IP20 |
| Operating Voltage | 240 |
| Power Consumption | 160 W Nominal, 220 W Maximum |
| Power Options | None |
| Weight (kg) | 11.2 |
| Dimensions - Length (mm) | 435 |
| Width (mm) | 350 |
| Depth (mm) | 315 |
| Product ID | ARRI L7-C |
| ORDER CODE | LSF-AL7C |

ARRI 300 PLUS



| | |
|--------------------------|-----------------|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | None |
| Wattage | 300W |
| Beam Angle | 14° - 53° |
| White/Colour Temperature | 3200 K |
| Lamp | CP81 |
| IP Rating | IP20 |
| Operating Voltage | 240 |
| Power Consumption | 300W |
| Power Options | None |
| Weight (kg) | 1.8 |
| Dimensions - Length (mm) | 233 |
| Width (mm) | 187 |
| Depth (mm) | 160 |
| Product ID | ARRI 300 PLUS |
| ORDER CODE | LSF-A300 |



Studio Due Archiled 300



| | |
|--------------------------|------------------------|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | 16A Cee Form |
| Wattage | 210W |
| Beam Angle | 23° |
| White/Colour Temperature | Full colour mixing |
| Lamp | 96x 5W high power LEDs |
| IP Rating | IP54 |
| Operating Voltage | 240 |
| Power Consumption | 250W |
| Power Options | None |
| Weight (kg) | 10 |
| Dimensions - Length (mm) | 400 |
| Width (mm) | 354 |
| Depth (mm) | 197 |
| Product ID | ARCHILED 300 |
| ORDER CODE | LSF-AR300 |

Studio Due Archiled 150/C RGBA



| | |
|--------------------------|----------------------------|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | None |
| Wattage | 90W |
| Beam Angle | 10° & 23° lenses available |
| White/Colour Temperature | Full colour mixing |
| Lamp | Multiple RGB LEDs |
| IP Rating | IP66 |
| Operating Voltage | 240 |
| Power Consumption | 90W |
| Power Options | None |
| Weight (kg) | 7.7 |
| Dimensions - Length (mm) | 343 |
| Width (mm) | 327 |
| Depth (mm) | 125 |
| Product ID | ARCHILED 150/C RGBA |
| ORDER CODE | LSF-AR150 |

Studio Due Space Flower 3000



| | |
|--------------------------|------------------------------|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | None |
| Wattage | 3200W |
| Beam Angle | 22° |
| White/Colour Temperature | 3,400 K |
| Lamp | STI 3000 Watt |
| IP Rating | IP23 |
| Operating Voltage | 240 |
| Power Consumption | 15A running, 30A at start-up |
| Power Options | None |
| Weight (kg) | 70 |
| Dimensions - Length (mm) | 772 |
| Width (mm) | 685 |
| Depth (mm) | 450 |
| Product ID | SPACE FLOWER |
| ORDER CODE | LSF-SF3000 |

Studio Due CityColor 2500/C



| | |
|--------------------------|---------------------------|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | None |
| Wattage | 2700W |
| Beam Angle | 50° x 52° (50% intensity) |
| White/Colour Temperature | Full colour mixing |
| Lamp | 2500W Metal Halide |
| IP Rating | IP54 |
| Operating Voltage | 240 |
| Power Consumption | 2700W |
| Power Options | None |
| Weight (kg) | 71 |
| Dimensions - Length (mm) | 760 |
| Width (mm) | 790 |
| Depth (mm) | 580 |
| Product ID | CITY COLOR 2500/C |
| ORDER CODE | LSF-CC2500 |



Studio Due CityColor 1800



| | |
|--------------------------|---------------------------|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | None |
| Wattage | 2000W |
| Beam Angle | 50° x 52° (50% intensity) |
| White/Colour Temperature | Full colour mixing |
| Lamp | 1800W Metal Halide |
| IP Rating | IP54 |
| Operating Voltage | 240 |
| Power Consumption | 2000W |
| Power Options | None |
| Weight (kg) | 64.5 |
| Dimensions - Length (mm) | 760 |
| Width (mm) | 790 |
| Depth (mm) | 580 |
| Product ID | CITY COLOR 1800/C |
| ORDER CODE | LSF-CC1800 |

Par38 Uplighter



| | |
|--------------------------|-----------------|
| Incoming Connection | 16A Cee Form |
| Outgoing Connection | 16A Cee Form |
| Wattage | 60W - 120W |
| Beam Angle | 30° |
| White/Colour Temperature | 3,000 K |
| Lamp | PAR 38 |
| IP Rating | IP22 |
| Operating Voltage | 240 |
| Power Consumption | 120W (max.) |
| Power Options | None |
| Weight (kg) | 5 |
| Dimensions - Length (mm) | 295 |
| Width (mm) | 150 |
| Depth (mm) | 150 |
| Product ID | PAR38 UPLIGHTER |
| ORDER CODE | LSF-P38U |

110cm 5in1 Reflector

| | |
|--------------------------|------|
| Incoming Connection | N/A |
| Outgoing Connection | N/A |
| Wattage | N/A |
| Beam Angle | N/A |
| White/Colour Temperature | N/A |
| Lamp | N/A |
| IP Rating | N/A |
| Operating Voltage | N/A |
| Power Consumption | N/A |
| Power Options | N/A |
| Weight (kg) | 0.2 |
| Dimensions - Length (mm) | 1100 |
| Width (mm) | 1100 |
| Depth (mm) | 5 |
| Additional Notes | |

5 in 1 multi photo reflector disc 43 inches / 110 cm. It comes with silver, gold, black, white and translucent surfaces, as those are the most popular reflectors in photography. It also folds into an easy to carry pouch for added convenience.

| | |
|------------|-------------------|
| Product ID | NEEWER 5IN1 110CM |
| ORDER CODE | LSF-N110R |





TOWERLIGHT RENTAL GUIDE

Working with you to make your event happen



Luminator



| | | |
|------------------------------------|--|-------------------|
| Generator Size (kW) | N/A | |
| Incoming Connection(s) | 16A Cee Form | |
| Outgoing Connection | 16A Cee Form | |
| Lighting Heads | 4x 250W Metal Halide | |
| RCD Protection | ✗ | |
| Mast Operating System | Electronic | |
| Petrol or Diesel | N/A | |
| Fuel Tank Capacity | N/A | |
| Fuel Consumption | N/A | |
| Noise Level @ 1 Meter and 7 Metres | 1m | 7m |
| | Unspecified | Unspecified |
| Weight | With Fuel (kg) | Without Fuel (kg) |
| | N/A | 132 |
| Open Dimensions Length (mm) | 2500 | |
| Width (mm) | 2500 | |
| Height (mm) | 5000 | |
| Closed Dimensions Length (mm) | 400 | |
| Width (mm) | 400 | |
| Height (mm) | 1880 | |
| Fork Truck Pockets | ✗ | |
| Single Point Lift | ✗ | |
| Manual Start | N/A | |
| Variations | None | |
| Road Tow Option | N/A | |
| Additional Notes | Using 1000W of power, several Luminators can be powered from one supply. Light heads tilt for 360° or 180° | |
| Product ID | LLU | |
| ORDER CODE | LTL-LUM | |

Road Tow Towerlight



| | | |
|------------------------------------|--------------------------------------|-------------------|
| Generator Size (kW) | 5 kW | |
| Incoming Connection(s) | None | |
| Outgoing Connection | 1x 16A 230V | |
| Lighting Heads | 5x 240W LED | |
| RCD Protection | ✓ | |
| Mast Operating System | Hydraulic System: Bio-degradable oil | |
| Petrol or Diesel | Diesel | |
| Fuel Tank Capacity | 130 Litres | |
| Fuel Consumption | 0.97L/hr (Lamps only) | |
| Noise Level @ 1 Meter and 7 Metres | 1m | 7m |
| | 98 dB(A) | 60dB(A) |
| Weight | With Fuel (kg) | Without Fuel (kg) |
| | 1050 | 933 |
| Open Dimensions Length (mm) | 2870 | |
| Width (mm) | 2639 | |
| Height (mm) | 8740 | |
| Closed Dimensions Length (mm) | 2565 | |
| Width (mm) | 1320 | |
| Height (mm) | 2100 | |
| Fork Truck Pockets | ✓ | |
| Single Point Lift | ✓ | |
| Manual Start | ✓ | |
| Variations | None | |
| Road Tow Option | ✓ | |
| Additional Notes | | |
| Product ID | PLT | |
| ORDER CODE | LTL-RT90 | |



Static Towerlight



| | | |
|------------------------------------|--------------------------------------|-------------------|
| Generator Size (kW) | 5 kW | |
| Incoming Connection(s) | None | |
| Outgoing Connection | 2 x 16A Cee Form | |
| Lighting Heads | 4x 1000W Halide Lights | |
| RCD Protection | ✓ | |
| Mast Operating System | Hydraulic System: Bio-degradable oil | |
| Petrol or Diesel | Diesel | |
| Fuel Tank Capacity | 130 Litres | |
| Fuel Consumption | 1.53 L/hr (Lamps Only) | |
| Noise Level @ 1 Meter and 7 Metres | 1m | 7m |
| | 98 dB(A) | 61dB(A) |
| Weight | With Fuel (kg) | Without Fuel (kg) |
| | 1050 | 933 |
| Open Dimensions | 2000 | |
| Length (mm) | | |
| Width (mm) | 2600 | |
| Height (mm) | 9000 | |
| Closed Dimensions | 1450 | |
| Length (mm) | | |
| Width (mm) | 1100 | |
| Height (mm) | 2140 | |
| Fork Truck Pockets | ✓ | |
| Single Point Lift | ✓ 4 point lift | |
| Manual Start | ✓ | |
| Variations | Road Tow & Static Versions | |
| Road Tow Option | ✓ | |
| Additional Notes | | |
| Product ID | PLS | |
| ORDER CODE | LTL-S | |

Linklight



| | | |
|------------------------------------|---|-------------------|
| Generator Size (kW) | N/A | |
| Incoming Connection(s) | 32a 2P+E | |
| Outgoing Connection | 32a 2P+E | |
| Lighting Heads | 4x 1000W Halide Lights | |
| RCD Protection | ✗ | |
| Mast Operating System | Manual Winch | |
| Petrol or Diesel | N/A | |
| Fuel Tank Capacity | N/A | |
| Fuel Consumption | N/A | |
| Noise Level @ 1 Meter and 7 Metres | 1m | 7m |
| | N/A | N/A |
| Weight | With Fuel (kg) | Without Fuel (kg) |
| | N/A | 244 |
| Open Dimensions | 1800 | |
| Length (mm) | | |
| Width (mm) | 1800 | |
| Height (mm) | 7000 | |
| Closed Dimensions | 1200 | |
| Length (mm) | | |
| Width (mm) | 800 | |
| Height (mm) | 2330 | |
| Fork Truck Pockets | ✓ | |
| Single Point Lift | ✓ (multiple lift eyes) | |
| Manual Start | N/A | |
| Variations | None | |
| Road Tow Option | N/A | |
| Additional Notes | Up to four Link Lights can be linked together and powered from a single source - lighting up an area with just 1 supply. Easy and cost effective to transport, the Link Light can be set up by a single person, saving time and manpower. | |
| Product ID | LLI-01 | |
| ORDER CODE | LTL-LINK | |