

EST  1999

Powerline

POWER DISTRIBUTION TEMPERATURE CONTROL



TOWERLIGHT RENTAL GUIDE

Working with you to make your event happen

— www —

THEPOWERLINE.CO.UK



Luminator



Generator Size (kW)	N/A	
Incoming Connection(s)	16A Cee Form	
Outgoing Connection	16A Cee Form	
Lighting Heads	4x 250W Metal Halide	
RCD Protection	✗	
Mast Operating System	Electronic	
Petrol or Diesel	N/A	
Fuel Tank Capacity	N/A	
Fuel Consumption	N/A	
Noise Level @ 1 Meter and 7 Metres	1m	7m
	Unspecified	Unspecified
Weight	With Fuel (kg)	Without Fuel (kg)
	N/A	132
Open Dimensions Length (mm)	2500	
Width (mm)	2500	
Height (mm)	5000	
Closed Dimensions Length (mm)	400	
Width (mm)	400	
Height (mm)	1880	
Fork Truck Pockets	✗	
Single Point Lift	✗	
Manual Start	N/A	
Variations	None	
Road Tow Option	N/A	
Additional Notes	Using 1000W of power, several Luminators can be powered from one supply. Light heads tilt for 360° or 180°	
Product ID	LLU	
ORDER CODE	LTL-LUM	

Road Tow Towerlight



Generator Size (kW)	5 kW	
Incoming Connection(s)	None	
Outgoing Connection	1x 16A 230V	
Lighting Heads	5x 240W LED	
RCD Protection	✓	
Mast Operating System	Hydraulic System: Bio-degradable oil	
Petrol or Diesel	Diesel	
Fuel Tank Capacity	130 Litres	
Fuel Consumption	0.97L/hr (Lamps only)	
Noise Level @ 1 Meter and 7 Metres	1m	7m
	98 dB(A)	60dB(A)
Weight	With Fuel (kg)	Without Fuel (kg)
	1050	933
Open Dimensions Length (mm)	2870	
Width (mm)	2639	
Height (mm)	8740	
Closed Dimensions Length (mm)	2565	
Width (mm)	1320	
Height (mm)	2100	
Fork Truck Pockets	✓	
Single Point Lift	✓	
Manual Start	✓	
Variations	None	
Road Tow Option	✓	
Additional Notes		
Product ID	PLT	
ORDER CODE	LTL-RT90	



Static Towerlight



Generator Size (kW)	5 kW	
Incoming Connection(s)	None	
Outgoing Connection	2 x 16A Cee Form	
Lighting Heads	4x 1000W Halide Lights	
RCD Protection	✓	
Mast Operating System	Hydraulic System: Bio-degradable oil	
Petrol or Diesel	Diesel	
Fuel Tank Capacity	130 Litres	
Fuel Consumption	1.53 L/hr (Lamps Only)	
Noise Level @ 1 Meter and 7 Metres	1m	7m
	98 dB(A)	61dB(A)
Weight	With Fuel (kg)	Without Fuel (kg)
	1050	933
Open Dimensions Length (mm)	2000	
Width (mm)	2600	
Height (mm)	9000	
Closed Dimensions Length (mm)	1450	
Width (mm)	1100	
Height (mm)	2140	
Fork Truck Pockets	✓	
Single Point Lift	✓ 4 point lift	
Manual Start	✓	
Variations	Road Tow & Static Versions	
Road Tow Option	✓	
Additional Notes		
Product ID	PLS	
ORDER CODE	LTL-S	

Linklight



Generator Size (kW)	N/A	
Incoming Connection(s)	32a 2P+E	
Outgoing Connection	32a 2P+E	
Lighting Heads	4x 1000W Halide Lights	
RCD Protection	✗	
Mast Operating System	Manual Winch	
Petrol or Diesel	N/A	
Fuel Tank Capacity	N/A	
Fuel Consumption	N/A	
Noise Level @ 1 Meter and 7 Metres	1m	7m
	N/A	N/A
Weight	With Fuel (kg)	Without Fuel (kg)
	N/A	244
Open Dimensions Length (mm)	1800	
Width (mm)	1800	
Height (mm)	7000	
Closed Dimensions Length (mm)	1200	
Width (mm)	800	
Height (mm)	2330	
Fork Truck Pockets	✓	
Single Point Lift	✓ (multiple lift eyes)	
Manual Start	N/A	
Variations	None	
Road Tow Option	N/A	
Additional Notes	Up to four Link Lights can be linked together and powered from a single source - lighting up an area with just 1 supply. Easy and cost effective to transport, the Link Light can be set up by a single person, saving time and manpower.	
Product ID	LLI-01	
ORDER CODE	LTL-LINK	