

EST ⚡ 1999
Powerline

POWER DISTRIBUTION TEMPERATURE CONTROL



EXTERIOR AND FLOOD LIGHT RENTAL GUIDE

Working with you to make your event happen

— www —
THEPOWERLINE.CO.UK



150W Enclosed Halogen Floodlight



Incoming Connection	16A
Wattage Lamp Type	150W K12
IP Rating	IP54
Variations	None
Weight (kg)	0.75
Dimensions - Length (mm)	135
Width (mm)	95
Depth (mm)	120
ORDER CODE	LEF150TH

400W Enclosed Halogen Floodlight



Incoming Connection	16A
Wattage Lamp Type	400W K1
IP Rating	IP54
Compatible with	120W - 230W - 300W - 400W bulbs
Weight (kg)	1.75
Dimensions - Length (mm)	180
Width (mm)	140
Depth (mm)	125
ORDER CODE	LEF400TH

1000W Enclosed Halogen Floodlight



Incoming Connection	16A
Wattage Lamp Type	1000W K4
IP Rating	IP54
Variations	None
Weight (kg)	2.2
Dimensions - Length (mm)	250
Width (mm)	270
Depth (mm)	150
ORDER CODE	LEF1000TH

1500W Enclosed Halogen Floodlight



Incoming Connection	16A
Wattage Lamp Type	1500W K5
IP Rating	IP54
Variations	None
Weight (kg)	4
Dimensions - Length (mm)	350
Width (mm)	390
Depth (mm)	180
ORDER CODE	LEF1500TH

70W Metal Halide Floodlight



Incoming Connection	16A
Wattage Lamp Type	70W HQI-TS
IP Rating	IP65
Colours Available	White - Sodium - Blue - Green - Magenta
Weight (kg)	5.4
Dimensions - Length (mm)	370
Width (mm)	240
Depth (mm)	100
ORDER CODE	LEF70 (W-S-B-G-M Colour)

150W Metal Halide Floodlight



Incoming Connection	16A
Wattage Lamp Type	150W HQI-TS
IP Rating	IP65
Colours Available	White - Sodium - Blue - Green - Magenta
Weight (kg)	5.4
Dimensions - Length (mm)	370
Width (mm)	240
Depth (mm)	100
ORDER CODE	LEF150 (W-S-B-G-M Colour)



250W Metal Halide Floodlight



Incoming Connection	16A
Wattage Lamp Type	250W HQI-TS
IP Rating	IP65
Colours Available	White - Sodium - Blue - Green - Magenta
Weight (kg)	8
Dimensions - Length (mm)	500
Width (mm)	410
Depth (mm)	140
ORDER CODE	LEF250 (W-S-B-G-M Colour)

400W Metal Halide Floodlight



Incoming Connection	16A
Wattage Lamp Type	400W HQI-TS
IP Rating	IP65
Colours Available	White - Sodium - Blue - Green - Magenta
Weight (kg)	8.75
Dimensions - Length (mm)	500
Width (mm)	410
Depth (mm)	140
ORDER CODE	LEF400 (W-S-B-G-M Colour)

70W SON Floodlight



Incoming Connection	16A
Wattage Lamp Type	70W E27 ES
IP Rating	IP54
Variations	None
Weight (kg)	3.5
Dimensions - Length (mm)	370
Width (mm)	240
Depth (mm)	140
ORDER CODE	LEF70SON

GU10 Spike Light



Incoming Connection	16A
Wattage Lamp Type	Up to 50W GU10 50W (max.)
IP Rating	IP65
Variations	Various LED colours available
Weight (kg)	0.75
Dimensions - Length (mm)	150
Width (mm)	100
Depth (mm)	100
ORDER CODE	LEFGU10SL

PAR 38 Spike



Incoming Connection	16A
Wattage Lamp Type	80W (120W White)* PAR 38
IP Rating	IP44
Variations	White* - Green - Blue - Yellow - Red
Weight (kg)	1.16
Dimensions - Length (mm)	100
Width (mm)	130
Depth (mm)	90
ORDER CODE	LEFPAR38 (W-G-B-Y-R Colour)

10W LED Floodlight



Incoming Connection	16A
Wattage Lamp Type	10W LED
IP Rating	IP65
Variations	N/A
Weight (kg)	0.75
Dimensions - Length (mm)	100
Width (mm)	130
Depth (mm)	90
ORDER CODE	LEF10LED



20W LED Floodlight



Incoming Connection	16A
Wattage Lamp Type	20W LED
IP Rating	IP65
Weight (kg)	0.75
Dimensions - Length (mm)	100
Width (mm)	130
Depth (mm)	90
ORDER CODE	LEF20LED

30W LED Floodlight



Incoming Connection	16A
Wattage Lamp Type	30W LED
IP Rating	IP65
Total Light Output	3000lm
Dimensions - Length (mm)	190
Width (mm)	274
Depth (mm)	42
ORDER CODE	LEF30LED

50W LED Floodlight



Incoming Connection	16A
Wattage Lamp Type	50W LED
Total Light Output	5000lm
IP Rating	IP65
Dimensions - Length (mm)	187
Width (mm)	216
Depth (mm)	62
ORDER CODE	LEF50LED

100W LED Floodlight



Incoming Connection	16A
Wattage Lamp Type	100W LED
Total Light Output	up to 20000lm
IP Rating	IP65
Dimensions - Length (mm)	237
Width (mm)	247
Depth (mm)	82
ORDER CODE	LEF100LED

NOTES
