

EST  1999

Powerline

POWER DISTRIBUTION TEMPERATURE CONTROL



UPS RENTAL GUIDE

Working with you to make your event happen

— www —

THEPOWERLINE.CO.UK



UPS 3 kVA

Size (kVA)	3
Incoming Phase	1Ø
Outgoing Phase	1Ø
Incoming Connections	16A C20 IEC
Outgoing Connections	1 x C20 IEC 8 x C13 IEC
Incoming Voltage	230
Outgoing Voltage	230
Run time mins	10 at full load
Dimensions - Length (mm)	520
Width (mm)	190
Height (mm)	33
Weight (kg)	28
Wheels	X
ORDER CODE	UPS3

UPS 6 kVA

Size (kVA)	6
Incoming Phase	1Ø
Outgoing Phase	1Ø
Incoming Connections	32/1 Cee Form
Outgoing Connections	32/1 Cee Form
Incoming Voltage	230
Outgoing Voltage	230
Run time mins	5.5 at full load
Dimensions - Length (mm)	720
Width (mm)	250
Height (mm)	660
Weight (kg)	77
Wheels	✓
ORDER CODE	UPS6

UPS 15 kVA



Size (kVA)	15
Incoming Phase	3Ø
Outgoing Phase	3Ø
Incoming Connections	63/3 Cee Form
Outgoing Connections	63/3 Cee Form
Incoming Voltage	400
Outgoing Voltage	400
Run time mins	10 at full load
Dimensions - Length (mm)	1200 case, 1010 UPS
Width (mm)	590
Height (mm)	1610
Weight (kg)	410
Wheels	✓
ORDER CODE	UPS15



REMOTE MONITORING

Powerline are continually investing in the latest technology, so as to provide our clients with the very best solution the industry can offer. We are now able to offer remote monitoring solutions for UPS, Hybrid Generator and Generator rentals. This allows 24/7 real-time monitoring, providing remote control, text and email alerts to be configured along with fuel monitoring. All telemetry data is stored and can be reported on making sure we are providing the best solution.



- Remote control
- Configurable email alerts
- Configurable text alerts
- Historical data archive
- Comprehensive data reporting
- Real-time load monitoring